

Language

European Configuration A: English, German, Italian, French, Polish, Russian
European Configuration B: Netherlands, Sweden, Finland, Turkey, Denmark, Norway
American Configuration: English, Spanish, Portuguese, French
Asia Configuration A: English, Traditional Chinese, Simplified Chinese
Asia Configuration B: English, Japanese, Korean



Test range

CCA	100~2000	JIS	26A17~245H52
DIN	100~1400	CA	100~2000
EN	100~2000	MCA	100~2000
IEC	100~1400	BCI	100~2000
SAE	100~2000	GB	30Ah~200Ah

Technical Data

Display	4-line Graphic Lcd Display With Backlight
Test Cable	80 Cm Standard Cable
Working Temperature	-20~55°C(Test Temperature)/0~50°C(Print Temperature)
Dimension	188*95*41mm
Weight	450g
Case Material	Abs Acid-proof Plastic, Industrial Case Design, Suitable For Repair Workshops

● Applicable Vehicle

Car, motorcycles, lawn mowers and other gardening machines, Group 31, commercial vehicles 4D/8D

● Applicable battery types

6V, 12 V and 24V batteries (Lead-acid battery, gel battery and AGM battery)

● Optional accessories

Storage case

Thermal paper(sold in most office supply stores)